



US00RE45386E

(19) **United States**
 (12) **Reissued Patent**
 Marriott

(10) **Patent Number:** US RE45,386 E
 (45) **Date of Reissued Patent:** Feb. 24, 2015

(54) **MEANS FOR REMOVING UNWANTED IONS FROM AN ION TRANSPORT SYSTEM AND MASS SPECTROMETER**

(75) Inventor: Philip Marriott, Buxton (GB)

(73) Assignee: Thermo Fisher Scientific (Bremen) GmbH, Bremen (DE)

(21) Appl. No.: 14/032,096

(22) Filed: Sep. 19, 2013

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: 7,202,470
 Issued: Apr. 10, 2007
 Appl. No.: 09/787,358
 PCT Filed: Sep. 16, 1999
 PCT No.: PCT/GB99/03076
 § 371 (c)(1),
 (2), (4) Date: May 15, 2001
 PCT Pub. No.: WO00/16375
 PCT Pub. Date: Mar. 23, 2000

(30) **Foreign Application Priority Data**

Sep. 16, 1998 (GB) 98202104

(51) **Int. Cl.**

H01J 49/00 (2006.01)
 H01J 49/26 (2006.01)
 B01D 59/44 (2006.01)

(52) **U.S. Cl.**

USPC 250/281; 250/282; 250/283; 250/287;
 250/423 R; 250/424; 315/111.81; 315/111.21

(58) **Field of Classification Search**

CPC H01J 49/105; H01J 49/421; H01J 49/02;
 H01J 49/062; H01J 49/0095; H01J 49/06
 USPC 250/281, 282, 283, 287, 423 R, 424;
 315/111.81, 111.21

See application file for complete search history.

(56)

References Cited

U.S. PATENT DOCUMENTS

3,129,327 A	4/1964	Brubaker
3,937,955 A	2/1976	Comisarow et al.
4,148,196 A	4/1979	French et al.
4,234,791 A	11/1980	Enke et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP	0237259 A2	9/1887
EP	0373835	6/1990

(Continued)

OTHER PUBLICATIONS

Agilent Technologies Inc., Publication No. 5968-8813E, Dec. 1999,
 pp. 1-12.

(Continued)

Primary Examiner — Nikita Wells

(74) *Attorney, Agent, or Firm* — Kilpatrick Townsend & Stockton LLP

(57)

ABSTRACT

The present invention relates to inductively coupled plasma mass spectrometry (ICPMS) in which a collision cell is employed to selectively remove unwanted artefact ions from an ion beam by causing them to interact with a reagent gas. The present invention provides a first evacuated chamber (6) at high vacuum located between an expansion chamber (3) and a second evacuated chamber (20) containing the collision cell (24). The first evacuated chamber (6) includes a first ion optical device (17). The collision cell (24) contains a second ion optical device (25). The provision of the first evacuated chamber (5) reduces the gas load on the collision cell (24), by minimising the residual pressure within the collision cell (24) that is attributable to the gas load from the plasma source (1). This serves to minimise the formation, or re-formation, of unwanted artefact ions in the collision cell (24).

50 Claims, 2 Drawing Sheets

